



000 «Полимер Экспорт»

ПРОМЫШЛЕННЫЕ ЛАКОКРАСОЧНЫЕ ПОКРЫТИЯ

8 (4932)773-503

raum-profile.ru
Inmarketing@gk-rp.ru



Release date: 14.08.2023
Manufacturer: Russian Federation
TC 20.30.22-005-69372620-2020

FORMULA THINNER «Polytex Slow»

CERTIFICATE	State Registration Certificate № RU.01.PA.02.008.E.000800.06.22 from 10.06.2022 Chemical safety data sheet from 20.06.2022								
DESCRIPTION	General purpose thinner for «Polytex» products when hot drying.								
FIELDS OF APPLICATION	It is used for thinning two-component polyurethane materials, mainly where hot drying is required. The thinner contains a high-boiling fraction to contribute to good filling, high gloss and high-quality paint film formation, even at elevated temperatures. This thinner helps to avoid such surface defects as shagreen, punctures and prevent solvent popping during coating formation. More detailed information for thinning can be found in products technical specifications.								
TECHNICAL DATA	<table><tr><td>Colour and appearance</td><td>Transparent liquid, does not contain foreign impurities.</td></tr><tr><td>Mass fraction of water, %, no more</td><td>0,05</td></tr><tr><td>Thinning action</td><td>No curdling or paint separation are allowed. No coat whitening and matt spots are allowed after drying</td></tr><tr><td>Density at 20°C, g/cm³</td><td>0,890-0,910</td></tr></table>	Colour and appearance	Transparent liquid, does not contain foreign impurities.	Mass fraction of water, %, no more	0,05	Thinning action	No curdling or paint separation are allowed. No coat whitening and matt spots are allowed after drying	Density at 20°C, g/cm ³	0,890-0,910
Colour and appearance	Transparent liquid, does not contain foreign impurities.								
Mass fraction of water, %, no more	0,05								
Thinning action	No curdling or paint separation are allowed. No coat whitening and matt spots are allowed after drying								
Density at 20°C, g/cm ³	0,890-0,910								
PACKAGE SIZE	Plastic can 10 l: 9 kg/10 l.								
STORAGE	Store in a tightly closed container in a dry room at a temperature from - 40 ° C to + 40 ° C away from sources of ignition, protecting from direct sunlight and moisture								
GUARANTED STORAGE LIFE	Expire date is 12 months in case if delivery and storing rules are followed. After expire date shouldn't be used without tests.								
HEALTH AND SAFETY	When painting work, use personal protective equipment (respirators, gloves, glasses, etc.). Work inside the room should be carried out with artificial (local, general) or natural ventilation. Use the thinner only in places without sources of open fire and ignition. Avoid contact with skin or eyes. In case of skin contact immediately wipe with a rag or cotton swab, rinse thoroughly with soapy water, do not use solvents. In case of eyes contact rinse with clean water for at least 10 minutes, consult a doctor. In case of ingestion, consult a doctor.								
COMPOSITION	Mixture of target thinners.								
RECYCLING	Packing materials are recycled as consumer waste.								

Further Information.

The recommendations above are based on our own research and our best knowledge but don't fully guarantee any particular case as it depends on the quality, friability and porosity of the base. The local working conditions and methods may vary and are beyond our control. Therefore we cannot be held responsible for the actual work on the site. The information is currently updating.



Собственное современное производство



Система Менеджмента Качества (ISO 9001)



Аттестованная лаборатория



На рынке с 2002 года