



ООО «Полимер Экспорт»

ПРОМЫШЛЕННЫЕ ЛАКОКРАСОЧНЫЕ ПОКРЫТИЯ

8 (4932)773-503



raum-profile.ru
Inmarketing@gk-rp.ru



Release date: 14.08.2023.
Manufacturer: Russian Federation
TC 20.30.22-005-69372620-2020

FORMULA THINNER «EPPEX»

CERTIFICATE

State Registration Certificate № RU.01.PA.02.008.E.000764.06.22 from 06.06.2022
Chemical safety data sheet from 20.06.2022

DESCRIPTION

General purpose thinner for «EPPEX» products.

FIELDS OF APPLICATION

Thinner is used to thin two components epoxy materials to working consistency. More detailed information for thinning can be found in products technical specifications.

TECHNICAL DATA

Colour and appearance	Transparent liquid, does not contain foreign impurities.
Mass fraction of water, %, no more	0,1
Thinning action	No curdling or paint separation are allowed. No coat whitening and matt spots are allowed after drying.
Density at 20°C, g/cm ³	0,840-0,860

PACKAGE SIZE

Plastic can 5 l:4,25 kg/5 l

STORAGE

Store in a tightly closed container in a dry room, at a temperature from - 40 °C to + 40 °C away from sources of ignition, protecting from direct sunlight and moisture

GUARANTEED STORAGE LIFE

Expire date is 12 months in case if delivery and storing rules are followed. After expire date shouldn't be used without tests.

HEALTH AND SAFETY

When painting work, use personal protective equipment (respirators, gloves, glasses, etc.). Work inside the room should be carried out with artificial (local, general) or natural ventilation. Use the thinner only in places without sources of open fire and ignition. Avoid contact with skin or eyes. In case of skin contact immediately wipe with a rag or cotton swab, rinse thoroughly with soapy water, do not use solvents. In case of eyes contact rinse with clean water for at least 10 minutes, consult a doctor. In case of ingestion, consult a doctor.

COMPOSITION

Mixture of target thinners.

RECYCLING

Packing materials are recycled as consumer waste.

Further Information.

The recommendations above are based on our own research and our best knowledge but don't fully guarantee any particular case as it depends on the quality, friability and porosity of the base. The local working conditions and methods may vary and are beyond our control. Therefore we cannot be held responsible for the actual work on the site. The information is currently updating.

